

# LIGHTING THE WAY FOR SIXTY YEARS



## ASSEMBLY INSTRUCTION MODEL ADD-312-AG-CL






Dress the glass from tier #7.



local electrical codes.



40 Watts Recommended 60 Watts Max. USE LED BULBS FOR EXTENDED USE This Fixture is Dry Rated

#### How to Install

- **1.** Decide the preferred hanging height and choose the correct number of rods needed.
- 2. Feed the wires and safety cable through the rods, screw collar ring and canopy. Screw the rods together. Screw one end of the rod assembly onto the top of frame and the other end onto the swivel on the mounting strap.
- 3. Place the mounting strap over the outlet box and mark the two points on the ceiling with same distance as between the two holes on the mounting strap.
- 4. Drill the holes at the marked points and insert the plastic anchors into the holes.
- 5. Raise the fixture up to the ceiling and wrap the safety cable around the mounting strap and secure with the locking device. When the wire connections are made, slip the canopy up along the rods and over the mounting strap. Secure with the screw collar ring.
- 6. Install the bulb into the socket.
- 7. Dress the glass as illustrated.

#### **Glass Sets**


1.61 pcs Clear glass 2 3/4x7 3/4"

WARNING: This product can expose you to Lead, which is known to the State of California to cause cancer and/or birth defects or reproductive harm. For more information go to www.P65Warnings.ca.gov





## PART NUMBER MODEL ADD-312-AG-CL



# Part Number

- A. (1)-Canopy,D 5 1/2XH1"
- D. (1)- 6" Rod XBN300AGROD6IN
- E. (3) 12" Rods XBN300AGROD12IN
- G. (61)-Glass,D2 3/4xH7 3/4" XBN300AGCLGLA7.75IN