## HINKLEY&R.

HINKLEY LIGHTING, INC. 33000 PIN OAK PARKWAY | AVON LAKE, OHIO 44012 [PH] 330.653.5500 [F] 440.653.5555 HINKLEYLIGHTING.com | FREDRICKRAMOND.com

## Small LED Vanity 52112BN

<ul> <li>outdoor no direct rain or sprinkler) location as defined by NEC and CEC. Meets Unit States UL Underwriters Laboratories &amp; CSA Canadian Standards Association Product Safety Standards</li> <li>Meets California Energy Commission 20 Title regulations</li> <li>Fixture is ADA compliant and adheres to the standards and guidelines listed by the Americans with Disabilities Act.</li> <li>Exclusively available in High Performance LED</li> </ul>		
MATERIAL       Metal         GLASS       Etched Opal         HEIGHT       3.0"         WIDTH       19.0"         LED COLOR TEMP       2700.0000         VOLTAGE       120v         LED LUMENS       1200         WATTAGE       15w LED *Included         TITLETWENTYFOURDERSC       CERTIFICATION         CERTIFICATION       C-US Damp Rated         EXTENSION       3.3"         TOP TO OUTLET       1.5"         BACK PLATE       6"W X 3"H         • Mounting hardware is hidden on the backplate to ensure a clean silhouette.         • Fixture can be mounted vertically         • Suitable for use in damp (interior moist a outdoor no direct rain or sprinkler) locatic as defined by NEC and CEC. Meets Unit States UL Underwriters Laboratories & CSA Canadian Standards Association Product Safety Standards         • Meets California Energy Commission 20 Title regulations         • Fixture is ADA compliant and adheres to the standards and guidelines listed by the Americans with Disabilities Act.         • Exclusively available in High Performance         LED		
GLASSEtched OpalHEIGHT3.0"WIDTH19.0"LED COLOR TEMP2700.0000VOLTAGE120vLED LUMENS1200WATTAGE15w LED *IncludedTITLETWENTYFOURD#EBCCERTIFICATIONC-US Damp RatedEXTENSION3.3"TOP TO OUTLET1.5"BACK PLATE6"W X 3"H• Mounting hardware is hidden on the backplate to ensure a clean silhouette. • Fixture can be mounted vertically • Suitable for use in damp (interior moist a outdoor no direct rain or sprinkler) locatio as defined by NEC and CEC. Meets Unit States UL Underwriters Laboratories & CSA Canadian Standards Association Product Safety Standards • Meets California Energy Commission 20 Title regulations • Fixture is ADA compliant and adheres to the standards and guidelines listed by the Americans with Disabilities Act. • Exclusively available in High Performance LED		
HEIGHT       3.0"         WIDTH       19.0"         LED COLOR TEMP       2700.0000         VOLTAGE       120v         LED LUMENS       1200         WATTAGE       15w LED *Included         TITLETWENTYFOURDERSC       CERTIFICATION         CERTIFICATION       C-US Damp Rated         EXTENSION       3.3"         TOP TO OUTLET       1.5"         BACK PLATE       6"W X 3"H         • Mounting hardware is hidden on the backplate to ensure a clean silhouette.         • Fixture can be mounted vertically         • Suitable for use in damp (interior moist a outdoor no direct rain or sprinkler) locatic as defined by NEC and CEC. Meets Unit States UL Underwriters Laboratories & CSA Canadian Standards Association Product Safety Standards         • Meets California Energy Commission 20 Title regulations         • Fixture is ADA compliant and adheres to the standards and guidelines listed by the Americans with Disabilities Act.         • Exclusively available in High Performance         LED		
WIDTH       19.0"         LED COLOR TEMP       2700.0000         VOLTAGE       120v         LED LUMENS       1200         WATTAGE       15w LED *Included         TITLETWENTYFOURDEFSC       CERTIFICATION         CERTIFICATION       C-US Damp Rated         EXTENSION       3.3"         TOP TO OUTLET       1.5"         BACK PLATE       6"W X 3"H         • Mounting hardware is hidden on the backplate to ensure a clean silhouette.         • Fixture can be mounted vertically         • Suitable for use in damp (interior moist a outdoor no direct rain or sprinkler) locatic as defined by NEC and CEC. Meets Unit States UL Underwriters Laboratories & CSA Canadian Standards Association Product Safety Standards         • Meets California Energy Commission 20 Title regulations         • Fixture is ADA compliant and adheres to the standards and guidelines listed by the Americans with Disabilities Act.         • Exclusively available in High Performance LED		•
LED COLOR TEMP       2700.0000         VOLTAGE       120v         LED LUMENS       1200         WATTAGE       15w LED *Included         TITLETWENTYFOURDEBC       CERTIFICATION         CERTIFICATION       C-US Damp Rated         EXTENSION       3.3"         TOP TO OUTLET       1.5"         BACK PLATE       6"W X 3"H         • Mounting hardware is hidden on the backplate to ensure a clean silhouette.         • Fixture can be mounted vertically         • Suitable for use in damp (interior moist a outdoor no direct rain or sprinkler) locatic as defined by NEC and CEC. Meets Unit States UL Underwriters Laboratories & CSA Canadian Standards Association Product Safety Standards         • Meets California Energy Commission 20 Title regulations         • Fixture is ADA compliant and adheres to the standards and guidelines listed by the Americans with Disabilities Act.         • Exclusively available in High Performance LED		
VOLTAGE       120v         LED LUMENS       1200         WATTAGE       15w LED *Included         TITLETWENTYFOURDEGSC       CERTIFICATION         CERTIFICATION       C-US Damp Rated         EXTENSION       3.3"         TOP TO OUTLET       1.5"         BACK PLATE       6"W X 3"H         • Mounting hardware is hidden on the backplate to ensure a clean silhouette.         • Fixture can be mounted vertically         • Suitable for use in damp (interior moist a outdoor no direct rain or sprinkler) locatic as defined by NEC and CEC. Meets Unit States UL Underwriters Laboratories & CSA Canadian Standards Association Product Safety Standards         • Meets California Energy Commission 20 Title regulations         • Fixture is ADA compliant and adheres to the standards and guidelines listed by the Americans with Disabilities Act.         • Exclusively available in High Performance LED	=	
LED LUMENS       1200         WATTAGE       15w LED *Included         TITLETWENTYFOURDEFBC       CERTIFICATION         CERTIFICATION       C-US Damp Rated         EXTENSION       3.3"         TOP TO OUTLET       1.5"         BACK PLATE       6"W X 3"H         • Mounting hardware is hidden on the backplate to ensure a clean silhouette.         • Fixture can be mounted vertically         • Suitable for use in damp (interior moist a outdoor no direct rain or sprinkler) location as defined by NEC and CEC. Meets Unit States UL Underwriters Laboratories & CSA Canadian Standards Association Product Safety Standards         • Meets California Energy Commission 20 Title regulations         • Fixture is ADA compliant and adheres to the standards and guidelines listed by the Americans with Disabilities Act.         • Exclusively available in High Performance LED		
WATTAGE       15w LED *Included         TITLETWENTYFOURDEBSC         CERTIFICATION       C-US Damp Rated         EXTENSION       3.3"         TOP TO OUTLET       1.5"         BACK PLATE       6"W X 3"H         • Mounting hardware is hidden on the backplate to ensure a clean silhouette.         • Fixture can be mounted vertically         • Suitable for use in damp (interior moist a outdoor no direct rain or sprinkler) locatic as defined by NEC and CEC. Meets Unit States UL Underwriters Laboratories & CSA Canadian Standards Association Product Safety Standards         • Meets California Energy Commission 20 Title regulations         • Fixture is ADA compliant and adheres to the standards and guidelines listed by the Americans with Disabilities Act.         • Exclusively available in High Performance LED		-
TITLETWENTYFOURDEBC         CERTIFICATION       C-US Damp Rated         EXTENSION       3.3"         TOP TO OUTLET       1.5"         BACK PLATE       6"W X 3"H         • Mounting hardware is hidden on the backplate to ensure a clean silhouette.         • Fixture can be mounted vertically         • Suitable for use in damp (interior moist a outdoor no direct rain or sprinkler) location as defined by NEC and CEC. Meets Unit States UL Underwriters Laboratories & CSA Canadian Standards Association Product Safety Standards         • Meets California Energy Commission 20 Title regulations         • Fixture is ADA compliant and adheres to the standards and guidelines listed by the Americans with Disabilities Act.         FEATURES AND		
CERTIFICATION       C-US Damp Rated         EXTENSION       3.3"         TOP TO OUTLET       1.5"         BACK PLATE       6"W X 3"H         • Mounting hardware is hidden on the backplate to ensure a clean silhouette.         • Fixture can be mounted vertically         • Suitable for use in damp (interior moist a outdoor no direct rain or sprinkler) location as defined by NEC and CEC. Meets Unit States UL Underwriters Laboratories & CSA Canadian Standards Association Product Safety Standards         • Meets California Energy Commission 20 Title regulations         • Fixture is ADA compliant and adheres to the standards and guidelines listed by the Americans with Disabilities Act.         • Exclusively available in High Performance LED	-	
EXTENSION       3.3"         TOP TO OUTLET       1.5"         BACK PLATE       6"W X 3"H         • Mounting hardware is hidden on the backplate to ensure a clean silhouette.         • Fixture can be mounted vertically         • Suitable for use in damp (interior moist a outdoor no direct rain or sprinkler) location as defined by NEC and CEC. Meets Unit States UL Underwriters Laboratories & CSA Canadian Standards Association Product Safety Standards         • Meets California Energy Commission 20 Title regulations         • Fixture is ADA compliant and adheres to the standards and guidelines listed by the Americans with Disabilities Act.         FEATURES AND		
TOP TO OUTLET       1.5"         BACK PLATE       6"W X 3"H         • Mounting hardware is hidden on the backplate to ensure a clean silhouette.         • Fixture can be mounted vertically         • Suitable for use in damp (interior moist a outdoor no direct rain or sprinkler) location as defined by NEC and CEC. Meets Unit States UL Underwriters Laboratories & CSA Canadian Standards Association Product Safety Standards         • Meets California Energy Commission 20 Title regulations         • Fixture is ADA compliant and adheres to the standards and guidelines listed by the Americans with Disabilities Act.         • Exclusively available in High Performance LED		•
BACK PLATE6"W X 3"H• Mounting hardware is hidden on the backplate to ensure a clean silhouette. • Fixture can be mounted vertically • Suitable for use in damp (interior moist a outdoor no direct rain or sprinkler) location as defined by NEC and CEC. Meets Unit States UL Underwriters Laboratories & CSA Canadian Standards Association Product Safety Standards • Meets California Energy Commission 20 Title regulations • Fixture is ADA compliant and adheres to the standards and guidelines listed by the Americans with Disabilities Act.FEATURES ANDExclusively available in High Performance LED		
<ul> <li>Mounting hardware is hidden on the backplate to ensure a clean silhouette.</li> <li>Fixture can be mounted vertically</li> <li>Suitable for use in damp (interior moist a outdoor no direct rain or sprinkler) locatic as defined by NEC and CEC. Meets Unit States UL Underwriters Laboratories &amp; CSA Canadian Standards Association Product Safety Standards</li> <li>Meets California Energy Commission 20 Title regulations</li> <li>Fixture is ADA compliant and adheres to the standards and guidelines listed by the Americans with Disabilities Act.</li> <li>Exclusively available in High Performance LED</li> </ul>		
<ul> <li>backplate to ensure a clean silhouette.</li> <li>Fixture can be mounted vertically</li> <li>Suitable for use in damp (interior moist a outdoor no direct rain or sprinkler) location as defined by NEC and CEC. Meets Unit States UL Underwriters Laboratories &amp; CSA Canadian Standards Association Product Safety Standards</li> <li>Meets California Energy Commission 20 Title regulations</li> <li>Fixture is ADA compliant and adheres to the standards and guidelines listed by the Americans with Disabilities Act.</li> <li>Exclusively available in High Performance LED</li> </ul>		
<ul> <li>Back plate height is 4.75" when mounted with optional junction box cover plate.</li> <li>Comes with optional Junction Box cover plate</li> <li>Extension is 3.25" when mounted withou optional junction box cover plate.</li> <li>For complete warranty information visit (hyperlink)</li> <li>15 year finish warranty</li> <li>LED components carry a 5-year limited warranty</li> <li>Angular lines, a bold finish, simple shape</li> </ul>	FEATURES AND BENEFITS	<ul> <li>backplate to ensure a clean silhouette.</li> <li>Fixture can be mounted vertically</li> <li>Suitable for use in damp (interior moist and outdoor no direct rain or sprinkler) locations as defined by NEC and CEC. Meets United States UL Underwriters Laboratories &amp; CSA Canadian Standards Association Product Safety Standards</li> <li>Meets California Energy Commission 2016 Title regulations</li> <li>Fixture is ADA compliant and adheres to the standards and guidelines listed by the Americans with Disabilities Act.</li> <li>Exclusively available in High Performance LED</li> <li>Back plate height is 4.75" when mounted with optional junction box cover plate.</li> <li>Comes with optional Junction Box cover plate</li> <li>For complete warranty information visit (hyperlink)</li> <li>15 year finish warranty</li> <li>LED components carry a 5-year limited warranty</li> <li>Angular lines, a bold finish, simple shape and sturdy details merge for a robust but pared down industrial design</li> </ul>
FINISH Brushed Nickel	FINISH	Brushed Nickel



AT HINKLEY, WE EMBRACE THE DESIGN PHILOSOPHY THAT YOU CAN MERGE TOGETHER THE LIGHTING, FURNITURE, ART, COLORS AND ACCESSORIES YOU LOVE INTO A BEAUTIFUL ENVIRONMENT THAT DEFINES YOUR OWN PERSONAL

STYLE. WE HOPE YOU WILL BE INSPIRED BY OUR COMMITMENT TO KEEP YOUR 'LIFE AGLOW.'

## *life* Aglow®